

# VVN

## Hydraulic excavators

Easymaintenance & outstanding after-sales services Complete line of applications and accessories Roll over protection system




## Models described in the catalog:


VVN HE 220 VVN HE 221 VVN HE 340


VVN HE 343 VVN HE 482

### **VVN HE 343**

### overall specifications







|                     |                             | 3237 10538   |
|---------------------|-----------------------------|--|
| Operating Weight    | Summary                     | Operating weight: 34300kg  The operating weight includes the weight of 6470mm boom, 2900mm standard arm, 1.6m³ bucket, 600mm track shoes, lubricating oil, coolant, the full tank and the rest standard configuration units. |
|                     | Ground pressure             | 68 kPa   |
| Bucket Capacity     | Standard                    | 1.6 m³ (Heavy duty)  |
|                     | Option range                | 1.6-2.2 m³   |
| Engine              | Model                       | Perkins 1206F-E70TTA (Euro IV)   |
|                     | Rated power                 | 205 kW (290 hp) /1950 rpm  |
|                     | Max. torque                 | 1219 N.m/1300 rpm  |
|                     | Displacement                | 7.1 L  |
| Hydraulic System    | Main pump                   | Axial variable piston pump   |
|                     | Max. flow of system         | 340×2 L/min  |
|                     | Max. pressure of Implements | 34.3 MPa   |
|                     | Max. pilot pressure         | 3.9 MPa  |
|                     | Swing motor                 | Piston Type (with safety valve and closed type brake)  |
|                     | Swing speed                 | 9.5 rpm  |
|                     | Travel motor                | Piston Type (with safety valve and closed type brake)  |
|                     | Travel speed                | 3.25/5.43 km/h   |
|                     | Gradeability                | 35°(70%)   |
|                     | Max. traction               | 298 kN   |
|                     | Max. arm digging force      | 178 kN   |
|                     | Max. bucket digging force   | 211 kN   |
| Fluid Capacity      | Fuel tank                   | 580 L  |
|                     | Hydraulic oil tank          | 390 L  |
| Undercarriage       | Standard track shoes width  | 600 mm   |
|                     | No. of track shoes          | 48 (each side)   |
|                     | No. of carrier rollers      | 2 (each side)  |
|                     | No. of track rollers        | 8 (each side)  |
| Electrical System   | System voltage              | 24 V   |
|                     | Battery capacity            | 12 V, 120 Ah×2   |
| Optional Equipments |                             | 700mm and 800mm width triple grouser shoes 5850mm boom 3200mm arm and 2600mm arm Hydraulic hammer and pipeline Quick-change coupler pipeline  Bidirectional auxiliary pipeline Anti-explosion valve Cab protecting nets      |



SIA "Viss Veikaliem un Noliktavām"
41A - 224 Kan davas street, Riga, LV-10 83
Phone: +371 27727449 (latvian, english),

+371 22074120 (I atvian, russian, english), +371 20330002 (latvian, russian, english)

E-mail: info@vvn.lv

LATVIA

LITHUANIA

Phone: +370 70066080 E-mail: info@vvnlt.lt www.vvnlt.lt ESTONIA

Phone: +372 634633 2, +372 63463 42 E-mail: info@wn.ee www.vvn.ee FINLAND

Phone: +358 7532633 23 E-mail: info@vvn.fi www.vvn.fi SWEDEN

Phone: +46 107502388 E-mail: info@vvngroup.se www.wngroup.se

NORWAY

Phone: +47 219558 68 E-mail: info@wngroup.no www.wngroup.no DENMARK

E-mail: info@vvngroup.dk www.vvngroup.dk RUSSIA

Phone: +7 84996092515 E-mail: info@vvngroup.ru www.vvngroup.ru BELARUS

Phone: +375 849960925 1 5 E-mail: info@vvngroup.by www.vvngroup.by