



TECHNICAL PARAMETERS

BASIC	Bucket Capacity	0.75m ³
	Rated Payload	1500kg
	Operating Weight	4520kg
	Traction Force	45kN
	Breakout Force	38kN
	L×W×H	5370×2100×2600mm
ENGINE	Manufacturer/Model	DEF20CDF4
	Rated Power	45kW/2400rpm
	Rated Torque	240N·m/1600-1800rpm
DRIVE TRAIN	Transmission Type	Countershaft Powershift
	Shift Type	Fixed Shaft Hydraulic Shift Spur Gear
	Pressure of Transmission	1.2-1.5MPa
	Gear	2F/2R
	Torque Converter	Single-stage, Single-turbine, 3-element
	Torque Ratio	3.2
	Main Reducer	Spiral Bevel Gear Single-stage Reduction
	Final Reducer	Planetary Reduction
	Tire	16/70-16
	Travel speed-Forward	16km/h
Travel speed-Reverse	16km/h	
BRAKE SYSTEM	Service Brake	Air Drive, Four Wheel Brake (Dry)
	Setting Pressure	0.78MPa
	Parking Brake	Flexible Shaft Controlled Drum brake
STEERING SYSTEM	Type	Hydraulic Load Sensor System
	Steering Pump	Shared With Working Pump
	System Pressure	14Mpa
HYDRAULIC SYSTEM	Type	Pilot Control
	Working Pump	Gear Pump
	Flow Rate	108L/min·2400rpm
	Control Valve	3 Spool
	System Pressure	16MPa
ELECTRIC SYSTEM	Cycle Time (Sec)	11.2
	System Voltage	12V
SERVICE REFILL CAPACITY	Battery (2 in series)	80Ah
	Fuel Tank	60L
SERVICE REFILL CAPACITY	Hydraulic Tank	60L
	Transmission	19L
	Front Axle / Rear Axle	20L

CONFIGURATION

YUN NEI Engine
LONKING Transmission
LONKING Torque Converter
Dry Brake Drive Axle
Pilot Working Control
Standard Working Equipment
Hydraulic Quick Hitch
MP3

OPTIONAL

Standard Bucket (3 Piece Cutting Edges)
Standard Bucket With an Integral Cutting Edge
Standard Bucket with Detachable Bucket Teeth
Enlarge Bucket 1.2m ³ , Detachable bucket Teeth
High Dump

For more information on Lonking products,
Please contact our local agent:

The following blank can be used for notes or comments.



CDM926 WHEEL LOADER

Efficiency Rules the Future

- RATED POWER: 45kW/2400rpm
- BUCKET CAPACITY: 0.75 m³
- RATED PAYLOAD: 1500kg
- OPERATING WEIGHT: 4520kg